



The classic balance with robust tuning fork measuring system

Features

- 1 KERN EG-N: **Internal adjustment** by rotary knob on the side. Guarantees high degree of accuracy and makes the balance independent of its location
- 2 KERN EW-N: **Adjusting program CAL** for quick setting of the balance accuracy using an external test weight
- Capacity display:** A bar lights up to show how much of the weighing range is still available
- Precise counting:** The automatic reference weight optimisation of reference weight gradually improves the average piece weight value
- GLP/ISO record keeping** of weight values
- Percentage determination**
- Weighing with tolerance range**

- Totalising** of pieces when counting
- Draught shield** standard for models with weighing plate size A, Weighing space W×D×H 158×130×78 mm

Technical data

- Large LCD display, digit height 17 mm
- Dimensions weighing surface, stainless steel
 - A Ø 118 mm, see larger picture
 - B W×D 170×140 mm
 - C W×D 180×160 mm
- Overall dimensions W×D×H, without draught shield
 - A, B 182×235×75 mm
 - C 192×275×87 mm
- Net weight approx. 1,4 kg
- Permissible ambient temperature 10 °C/30 °C


Accessories

- Protective working cover**, standard, can be re-ordered, scope of delivery: 5 items, for models with weighing plate size
 - A, B KERN EG-A05S05
 - C KERN EG-A09S05
- Precious stones plate**, aluminium with practical spout, W×D×H 83×66×23 mm, KERN AEJ-A05
- Rechargeable battery pack internal**, operating time up to 32 h without backlight, charging time approx. 12 h, for models with weighing plate size
 - A, B KERN EG-A04
 - C KERN EG-A06
- 2 **Large glass draught shield** with 3 sliding doors for easy access to the items being weighed. Weighing space W×D×H 150×140×130 mm, for models with weighing plate size A, KERN EG-A03
- Loop for underfloor weighing**, not included, for models with weighing plate size
 - A, B KERN EG-A07
 - C KERN EG-A08
- Further details, plenty of further accessories and suitable printers see *Accessories*

STANDARD



OPTION



FACTORY



Model	Weighing range [Max] g	Readout [d] g	Verification value [e] g	Minimal load [Min] g	Linearity g	Weighing plate	Options	
							Verification	DAkkS Calibr. Certificate
KERN							M KERN	DKD KERN
EW 220-3NM	220	0,001	-	-	± 0,002	A	-	963-127
EW 420-3NM	420	0,001	-	-	± 0,003	A	-	963-127
EW 620-3NM	620	0,001	-	-	± 0,003	A	-	963-127
EW 820-2NM	820	0,01	-	-	± 0,01	B	-	963-127
EW 2200-2NM	2200	0,01	-	-	± 0,01	C	-	963-127
EW 4200-2NM	4200	0,01	-	-	± 0,02	C	-	963-127
EW 6200-2NM	6200	0,01	-	-	± 0,03	C	-	963-128
EW 12000-1NM	12000	0,1	-	-	± 0,2	C	-	963-128

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

EG 220-3NM	220	0,001	0,01	0,02	± 0,002	A	965-216	963-127
EG 420-3NM	420	0,001	0,01	0,02	± 0,003	A	965-216	963-127
EG 620-3NM	620	0,001	0,01	0,1	± 0,004	A	965-201	963-127
EG 2200-2NM	2200	0,01	0,1	0,5	± 0,01	C	965-216	963-127
EG 4200-2NM	4200	0,01	0,1	0,5	± 0,02	C	965-216	963-127

KERN Pictograms:



Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven).



Piece counting: Reference quantities selectable. Display can be switched from piece to weight.



Rechargeable battery pack: Rechargeable set.



Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.



Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).



Universal mains adapter: with universal input and optional input socket adapters for
A) EU, GB
B) EU, GB, CH, USA
C) EU, GB, CH, USA, AUS



Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.



Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.



Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available.



Alibi memory: Electronic archiving of weighing results, complying with the 2014/31/EU standard.



Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition.



Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.



Data interface RS-232: To connect the balance to a printer, PC or network.



Weighing principle: Strain gauge
Electrical resistor on an elastic deforming body.



RS-485 data interface: To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.



Totalising level A: The weights of similar items can be added together and the total can be printed out.



Weighing principle: Tuning fork
A resonating body is electromagnetically excited, causing it to oscillate.



USB data interface: To connect the balance to a printer, PC or other peripherals.



Percentage determination: Determining the deviation in % from the target value (100 %).



Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings.



Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals.



Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.



Weighing principle: Single cell technology
Advanced version of the force compensation principle with the highest level of precision.



WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals.



Weighing with tolerance range: Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning.



Verification possible:
The time required for verification is specified in the pictogram.



Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.



Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value.



DAKkS calibration possible (DKD): The time required for DAKkS calibration is shown in days in the pictogram.



Interface for second balance: For direct connection of a second balance.



Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.



Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.



Network interface: For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.



ATEX explosion protection: Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device.



Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.



Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module.



Stainless steel: The balance is protected against corrosion.



Warranty: The warranty period is shown in the pictogram.



GLP/ISO log: The balance displays the weight, date and time, regardless of a printer connection.



Suspended weighing: Load support with hook on the underside of the balance.



GLP/ISO log: With weight, date and time. Only with KERN printers.



Battery operation: Ready for battery operation. The battery type is specified for each device.

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer:

EGITRON

Rua Central da Vergada, 1280
4535-166 MOZELOS VFR - PORTUGAL
Tel.: (+351) 227 471 120 - Fax: (+351) 227 471 129
info@egitron.pt - www.egitron.pt